

Sets for wooden doors



Tritec | Wood

Complete-sets, standard model t up to 1 3/4" height-adjustable approx. +/- 1/8", consisting of:

- 1 Guide rail, solid stainless steel, Ø 1", USO200EF length: see table
- 3 - 4 Wall attachments, stainless steel, USU215EF
- 2 Trolleys Tritec wood, stainless steel, USO123EF
- 2 Door stopper, stainless steel, USO251EF
- 1 Bottom guide, stainless steel, USH268K
- 1 Special tool for decorative screws, Z923
- 1 Installation instructions

Set numbers	Guide rail length inch	Passage width inch
USU65-1800EF	70 7/8"	29 1/2" - 35 7/16"
USU65-2100EF	82 11/16"	35 13/16" - 39 3/8"
USU65-2300EF	90 9/16"	39 3/4" - 44 1/16"
USU65-2540EF	100"	44 1/2" - 49 3/16"

▼ Wood drill holes Ø 3/8"

The maximum door weight is 100 kg (220 lbs)

For baseboards and trimmings, order spacer, (stainless steel, USO226-33EF) separately for each wall attachment, Cf. planning guide or page 21/22

You can find planning guides with drill hole sizes and installation instructions at www.beyerle-us.com

+ For special lengths for guide rails, other individual components and accessories, refer to page 24ff.

