## : Unotec Home | Glass

Complete-sets, standard model t = 5/16" - 1/2" consisting of:

- 1 Guide rail, solid stainless steel, ø 1", USO200EF length: see table
- 3 4 Wall attachments, stainless steel, USU210EF
- 2 Trolleys Unotec Home glass, stainless steel, USH100EF
- 2 Door stopper, stainless steel, USO250EF
- 1 Bottom guide, stainless steel, USO260EF
- 1 Special tool for decorative screws, Z923
- 1 Installation instructions

Set numbers	Guide rail length inch	Passage width inch
USU34-1800EF	70 7/8"	29 1/2" - 35 7/16"
USU34-2100EF	82 11/16"	35 13/16" - 39 3/8"
USU34-2300EF	90 9/16"	39 3/4" - 44 1/16"
USU34-2540EF	100"	44 1/2" - 49 3/16"

## ▼ Glass drill holes ø 1/2"

The maximum door weight is 100 kg (220 lbs)

For baseboards and trimmings, order spacer, (stainless steel, USO226-19EF) separately for each wall attachment, Cf. planning guide or page 21/22

You can find planning guides with drill hole sizes and installation instructions at www.beyerle-us.com

For special lengths for guide rails, other individual components and accessories, refer to page 24ff.











